


Agenda

- Trends in medical applications
- Role of PCI Express
- Altera® PCI Express solution
- PCI Express demo



CY2





Medical Sub-Segments

- Diagnostic imaging
 - Ultrasound (US)
 - Computed tomography (CT)
 - Magnetic resonance imaging (MRI)
 - Positron emission tomography (PET)
 - X-ray
- Electro-medical
 - Patient monitoring
 - Ventilation and life support
 - Anesthesia
- Cardiac rhythm management (CRM)
 - Automatic external defibrillators (AED)
 - Pacing systems
 - Implantable cardiac defibrillators (ICD)
- Other medical lab equipment
 - Scientific and lab instrumentation
 - Radiation











AED

Blood Analysis Centrifuge



Diagnostic Imaging Trends


Modality	Trend	
All	Trend towards digital imaging - higher resolution and 3-D imaging Increased amount of high-speed filtering	
	Trend towards serial backplanes	
	Portable imaging has potential to reach wider customer base	
СТ	Single slice to multi-slice	
MRI	Higher Tesla (T) based systems	
Ultrasound	Higher growth rates in developing nations due to lower system costs	
X-ray	Higher growth rates in developing nations due to lower system costs	
CT and PET	Evolution of combined modalities	
Nuclear/PET	The fastest growing modality – '03-'08 compound annual growth rate (CAGR) of 12%	





Our Customers Tell Us...

Healthcare Providers Driving Towards:



Medical OEM solutions

- Handheld and portable form factors
- **Flexible**
- Modular
- Cost-effective




solutions

Connectivity

Product Development Trends

- Market dynamics drive focus on differentiating via software and firmware
- Common hardware architectures are emerging:
 - a. Chassis-based, premium systems
 - b. Modular-based, mid-range systems
 - c. Handheld, value systems
- Architectural building blocks becoming standardized



Co-processing

Add-on features





Three Emerging Platforms

Chassis

- Leveraging PCIe/GbE for backplane interconnect
- High-end medical imaging

Modular

- Leveraging SBCs for software convenience and COTS hardware
- Patient monitoring, ultrasound, x-ray


Handheld

- Leveraging system-on-a-programmable-chip (SOPC)
 FPGAs
- Low-end patient monitoring/ultrasound



T&M Chassis System in 2008


- Asymmetric data flow
 - Scalable to smaller chassis
- Applications:
 - High-end medical imaging
 - CT, MR, PET
- Devices:
 - Acquisition: Cyclone[®] III FPGAs
 - Processing: Stratix[®] III FPGAs
 - Configuration and BIST: MAX® III **CPLDs**
- Competition:
 - FPGAs, ASICs, digital signal processing (DSP) devices





T&M Modular System in 2008

- Stackable modules
- Applications:
 - Mobile equipment
 - Patient monitoring
 - Endoscopes
 - Ultrasound, x-ray
- Devices:
 - Low end: Cyclone III FPGAs
 - Stackable: Stratix III FPGAs
 - Configuration and BIST:
 MAX III CPLDs
- Competition:
 - GPPs, DSP devices, FPGAs, ASICs



Application dependent

· Signal interface

IF daughterboards

Application independent

PCIe FPGA board

100 MHz 300 MHz DDR2

DRAM

Signal acquisition


Flash

Signal processing





T&M Handheld Devices in 2008



Applications:

Low-end patient monitoring, portable ultrasound, endoscopes

Device:

Mid-range: Cyclone III; High-end: HardCopy® III, MPU, configuration and BIST: MAX III


Competition:

Low-end: MCUs, DSP devices, ASICs





Video and Image Processing Suite




Video hardware platforms – development kits and reference designs





Deliver Faster Results and Lower Cost

 Use Nios II embedded processor and SOPC Builder for system integration




1 Quarter Saved on Two-Year Project!



Complete Memory Solutions

Advanced FPGA Architecture

- DQS phase shift circuitry
- Six registers in I/Os
- Feature-rich PLLs and clock management



Development Kits and Hardware Reference Platforms

- Demo project
- Board design guidelines
- Schematic and Gerber files

Memory Controller MegaCore® intellectual property (IP)

- Open source datapath
- Reference designs
- GUI
- Included in the free IP base suite

Software Support


- Automatic generated constraints
- System-level timing analysis
- SPICE and IBIS simulation models

Device Handbook, Application Note

- Interface description
- Timing analysis
- Electrical analysis



DSP Blocks for DSP Algorithms



- Basic multiplier modes
 - -8x(9x9)
 - 6 x (12x12)
 - 4 x (18x18)
 - 2 x (36x36)
 - 2 x complex (18x18)
- Sum modes
 - 4 x sum of two (18x18)
 - 2 x sum of four (18x18)
- Accumulation
 - 2 x Acc
- Cascade modes
 - Input cascade
 - Output cascade
- Rounding
 - Unbiased and biased
- Saturation
 - Asymmetrical and symmetrical
- Barrel shifter
 - Arithmetic, logical, and rotational



External Memory Interfaces

 Stratix III FPGAs are the only FPGAs in the industry to offer DDR3 interfaces


	Device family	
		Stratix II FPGAs/ Stratix II GX FPGAs
Interconnect	Performance* **	Performance
DDRIII	400 MHz	N/A
DDRII	400 MHz	333 MHz
QDR II	350 MHz	300 MHz
QDR II+	400 MHz	N/A
RLDRAM II	400 MHz	300 MHz



^{**} Pending Characterization



PCI Express Configuration (x1, x4, x8)



© 2007 Altera Corporation—Public



Altera PCI Express Solutions

- Complete, easy-to-use PCI Express solutions
 - x1, x4 and x8 endpoints
 - Industry-leading design flow with Altera IP MegaCore function
 - Stratix II GX, Cyclone II, Stratix II, HardCopy II, and Stratix GX device family support
- Low-risk, hardware-verified solutions
 - Device characterization and PCI-SIG compliance workshops
 - 2 generations of FPGAs with embedded transceivers
 - Stratix GX FPGAs passed PCI-SIG compliance
 - Stratix II GX FPGAs passed PCI-SIG compliance
 - Development/demo boards

Fastest Time-To-Market with a Reliable PCI Express Endpoint Solution



PCI-SIG Compliance and Interoperability

Motherboard vendor	Result
Intel	Passed
HP	Passed
IBM	Passed
ATI	Passed
nVidia	Passed
VIA	Passed

Bridge/switch tested	Result
PLX	Passed
IDT	Passed

Test equipment vendor	Result
Wavecrest	Passed
Agilent	Passed
Catalyst	Passed
Tektronix	Passed
VMETRO	Passed
Intel	Passed
LeCroy	Passed
Interoperability	Result
Freescale PowerQUICC III	Passed
IDT Switches	Passed

Passed all the PCI-SIG Gold-Suite Compliance Tests with 100% Pass Rate



Reliability - Interoperability

- Partnered with Freescale to create and present joint working **PCI** Express solution
- Demonstrated Freescale PowerQUICC III-to-Altera Stratix II GX interoperation
- Verified working PCI Express interface for up to 8 lanes




Freescale	Altera
MPC8548E	
MPC8547E	
MPC8545E	Stratix II GX FPGA
MPC8543E	
MPC8641	
MPC8641D	
MPC8572E and future MPC85xx	
processors with PCI Express	




PCle Board

- EP2SGX90FF1508
- x8 PCI Express
- DDRII
 - 72 bit, 333 MHz
- **QDRII**
 - 36 bit, 300 MHz (350-MHz QDRII+)
- 2x SFP ports
- JTAG header
- 10/100/1G Ethernet
- 2x mezzanine connector
 - Up to 84 LVDS
 - Up to 6 transceivers
 - Up to 3 clocks
- SMA clock input
- PCI Express Development Kit Stratix II GX Edition DK-PCIE-2SGX90N (US \$2,995)





PCI Express IP Core



- PCI Express 1.1 compliance
- Support for up to 4 virtual channels (VCs)
- Configurable maximum payload up to 2 Kbytes
 - 128, 256, 512, 1024, or 2048 bytes
- Configurable retry buffer
- Optional end-to-end cyclic redundancy code (ECRC) generation/checking
- Optional advanced error reporting (AER)
- Flexible reference clock support (100, 125, or 156.25 MHz)



Summary

- PCI Express adopted in current and next generation medical systems
- Altera FPGAs provide comprehensive support for PCI **Express**
 - Arria[™] GX FPGAs for mainstream applications
 - Stratix II GX FPGAs for emerging high-performance applications
- Altera PCI Express solution proven in real systems
 - Complete PCI-SIG compliance
 - Characterization reports, development kits



